


Motor Rated Power			11000W	
Inverter Power Supply			400Vdc	
Description	Symbol	Unit		
Duty	-	-	S1	
Nominal Speed	n_n	rpm	3500	
Frequency (N° poles)	$f (2p)$	Hz	233.3 (8)	
Constant Voltage	K_e	Vrms/Krpm	72.0	
Instant Torque	T_i	Nm	65.0	
Instant Current	i_i	Arms	80.0	
Rated Torque S1	T_r	Nm	30.0	
Rated Current S1	I_r	Arms	30.0	
Short Circuit Current	I_{SC}	Arms	32.0	
Rotor Inertia	J_r	kg x m ²	0.0081	
Ambient Temperature	θ_a	°C	-15 ÷ +40	
Protection Degree	IP		IP 54	up to IP67
Insulation Class	-	-	F	
Thermal protection	-	-	PTY 84-130	Alternative to KTY 84-130
Cooling system			Liquid	


Speed-Torque & Speed Power Motor Curves (*)

SMAC 200-052



PRELIMINARY - Simulated Data

Current Map [Arms]



* MTPA – MTPV Field Weakening strategy control & Optimized Advance Angle
(Ref. Simulation temperature 20.0°C)

Simulation Only

Efficiency Map % (*)

